

JFS-12HP



GENERAL

RADIO REMOTE	Wireless Transmitter System/w Tethered Backup Remote
VIBRATOR	Standard
WATER TANK	1000L (264 Gal)
WATER PUMP	Hydraulic Power 20 bar (290 psi)
WEAR PARTS	Carbide
OUTRIGGER	Hydraulic Front & Rear
TOOL BOX	Standard
WEIGHT	31,660 lbs/14,360 kg (Model As Shown)

*Not to be used through boom pipe

Contact your sales rep for your chassis options.

Alliance Concrete Pumps Inc. reserves the right to make changes to all specifications

PUMP

OUTPUT:	Rod Side	115 m ³ /h (150 yd ³ /h)
	Piston Side	72 m ³ /h (94 yd ³ /h)
PRESSURE:	Rod Side	92 bar (1334 psi) †
	Piston Side	148 bar (2146 psi) †
STROKES PER MINUTE	Rod Side	30
	Piston Side	19
HARD CHROMED CONCRETE CYLINDER	200 mm x 1400 mm (8" X 83")	
S-TUBE SIZE	200 mm x 178 mm (8" x 7")	
OUTLET	152 mm (6" ZX)	
MAX. AGGREGATE SIZE	63 mm (2.5")	
HYDRAULIC PUMP	Rexroth Hydromatic A11VLO260	
HYDRAULIC SYSTEM PRESSURE	350 bar (5076 psi)	
SWITCHING SYSTEM	Hydraulic w/Manual Override	
LUBE SYSTEM (HOPPER)	Lincoln Automatic Greaser	
HOPPER CAPACITY	Reinforced Hopper 600 L (159 Gal)	

ALLIANCECONCRETEPUMPS.COM



USA OFFICE: 800 West Ridge Road, Linwood, PA 19061
Toll Free 1.888.584.7231 | Phone 610.584.7231 | Fax 610.584.7251

CANADA OFFICE: 26162 30A Avenue, Aldergrove, BC V4W 2W5
Toll Free 1.888.870.0908 | Phone 604.607.0908 | Fax 604.607.0903